

TOP SPEED WINCH – GEN2

SPECIFICATION Gen2 12000LB

Waterproof: IP68 Rating

Rated Max Line Pull: 12,000lbs (5454kgs) single-line

Motor: 6.5HP Series Wound

Control: Remote Switch, 12' (3.7m) lead

Gear Train: 3-Stage Planetary

Gear Ratio: 265:1

Clutch: Sliding Ring Gear

Brake: Automatic Out-Of-Drum

Drum Size: Φ 2.5" (63mm) x Length 10.0" (254mm)

Cable: Φ 9.5mm x 26m

Fairlead: 4-Way Roller Fairlead

Remote Control: Integrated wireless and wired remote Included

Recommended Battery: 650CCA Minimum for Winching

Battery Leads: 25mm² x 72" (1.83m)

Mounting Bolt Pattern: 10.0" (254mm) x 4.50" (114mm)

Overall Dimension: L 22.3" x W 5.4" x H9.4"

Packing Size: 61 x 35 x 26 cms

Weight (Cable Winch): N.W 37.80 Kgs. / G.W 41 Kgs.



Line pull	Lbs	0	3000	6000	9000	12000
	Kg	0	1363	2727	4090	5454
Line speed	Ft/min	24.60	11.48	8.86	7.22	5.58
	m/min	7.5	3.5	2.7	2.2	1.7
Motor	Amp	70	138	218	260	330

Layers of cable		1	2	3	4
Rated line pull per layer	Lbs	12000	9530	7929	6770
	Kg	5455	4332	3604	3077
Cable capacity	Ft	18	37	64	91.8
	M	5.4	11.4	19.4	28