

TOP SPEED WINCH – GEN2**SPECIFICATION Gen2 15500LB**

Waterproof: IP68 Rating

Rated Max Line Pull: 15,500lbs (7045kgs) single-line

Motor: 6.5HP Series Wound

Control: Remote Switch, 12' (3.7m) lead

Gear Train: 3-Stage Planetary

Gear Ratio: 430:1

Clutch: Sliding Ring Gear

Brake: Automatic Out-Of-Drum

Drum Size: Φ 3.45" (88mm) x Length 10.0" (254mm)

Cable: Φ 12mm x 26m

Fairlead: 4-Way Roller Fairlead

Remote Control: Integrated wireless and wired remote Included

Recommended Battery: 650CCA Minimum for Winching

Battery Leads: 25mm² x 72" (1.83m)

Mounting Bolt Pattern: 10.0" (254mm) x 4.50" (114mm)

Overall Dimension: L 22.3"x W7.5" x H10.7"

Packing Size: 63 x 37 x 38cms

Weight (Cable Winch): N.W 54.20Kgs. / G.W 56.60Kgs.



Line pull	Lbs	No Load	4000	7500	11250	15000
	Kg	No Load	1814	3409	5113	6818
Line speed	Ft/min	23.62	10.50	8.20	5.25	3.94
	m/min	7.2	3.2	2.5	1.6	1.2
Motor	Amp	71	152	239	332	422

Layers of cable		1	2	3	4
Rated line pull per layer	Lbs	15000	12060	10082	8662
	Kg	6818	5482	4583	3937
Cable capacity	Ft	19.68	45.92	75.44	85.28
	M	6	14	23	26