

TOP SPEED WINCH – GEN2**SPECIFICATION 17500LB**

Waterproof: IP68 Rating

Rated Max Line Pull: 17,500lbs (7954kgs) single-line

Motor: 6.6HP Series Wound

Control: Remote Switch, 12' (3.7m) lead

Gear Train: 3-Stage Planetary

Gear Ratio: 430:1

Clutch: Sliding Ring Gear

Brake: Automatic Out-Of-Drum

Drum Size: Φ 3.45" (88mm) x Length 10.0" (254mm)

Cable: Φ 12mm x 26m

Fairlead: 4-Way Roller Fairlead

Remote Control: Integrated wireless and wired remote Included

Recommended Battery: 650CCA Minimum for Winching

Battery Leads: 25mm² x 72" (1.83m)

Mounting Bolt Pattern: 10.0" (254mm) x 4.50" (114mm)

Overall Dimension: L 22.3" x W 7.5" x H10.7"

Packing Size: 63 x 37 x 38 cms

Weight (Cable Winch): N.W 54.20 Kgs. / G.W 56.60 Kgs.



Line pull	Lbs	No Load	6000	10000	12000	14000	17000
	Kg	No Load	2721	4536	5454	6363	7727
Line speed	Ft/min	23.62	9.18	5.9	4.92	4.26	2.95
	m/min	7.2	2.8	1.8	1.5	1.3	0.9
Motor	Amp	71	200	300	350	395	450

Layers of cable		1	2	3	4
Rated line pull per layer	Lbs	17000	15225	13246	11524
	Kg	7727	6920	6021	5238
Cable capacity	Ft	19.68	45.92	75.44	85.28
	M	6	14	23	26